






CK 150 C 50/(60)Hz

CK

- Duct fan with circular connection.
- Proven performance and reliability.
- Compact with high capacity and efficiency.
- Low sound levels.
- Impeller with backward curved blades.
- The external rotor motor has maintenance-free sealed ball-bearings.
- Integrated motor protection.
- Junction box has enclosure class IP 54.
- For speed control a transformer or electronic speed controller can be connected.
- Fan housing is manufactured from galvanized sheet steel.
- The fan is intended to be installed in a duct system.
- When duct connected the fan can be installed outside or in damp environments.
- Easy installation in any position.



Voltage steps

1	2	3	4	5
80V	110V	135V	165V	230V

TECHNICAL DATA

7000045
CK 150 C aut tp

Voltage	230 V
Phase	1 ~
Frequency	50 Hz
Optional frequency	60 Hz
Power	105 W
Current	0.46 A
Speed	2580 r.p.m.
Max. temperature of transported air	75 °C
Max. temperature of transported air when speed controlled	75 °C
Sound pressure level at 3 m	43 dB(A)
Weight	4 kg
Enclosure class	44 IP
Insulation class, motor	F
Capacitor	3 µF
Duct connection	150 mm
Max. flow	706 m³/h
Max. pressure	393 Pa
Voltage range	220-240 V

SOUND DATA

	Flow (m³/h)	L _{WA} tot dB (A)	63Hz	125Hz	250Hz	500Hz	1KHz	2KHz	4KHz	8KHz
5. Surrounding Lw dB(A) 230V	428	50	21	35	45	43	45	36	36	28
5. Outlet Lw dB(A) 230V	428	73	56	64	67	67	65	61	60	53
5. Inlet Lw dB(A) 230V	428	74	54	64	70	70	66	62	60	53
4. Inlet Lw dB(A) 165V	360	70	51	62	66	65	62	57	54	46
3. Inlet Lw dB(A) 135V	281	65	49	59	60	59	55	51	46	37
2. Inlet Lw dB(A) 110V	220	57	41	51	53	52	47	41	36	26
1. Inlet Lw dB(A) 80V	144	49	35	46	43	40	35	26	27	21

DIMENSIONS

