

Carrier splitunits



turn to the experts™ 

38QUS028-042D8S buitendelen inverter
38QUS multi-split R32



Overzicht 38QUS028-042D8S inverter

Model buitendeel	38QUS	028D8S4	036D8S4	042D8S5
Gegevens buitendeel				
Koelcapaciteit	kW	8,2	10,2	12,0
Verwarmingscapaciteit	kW	8,7	11,0	12,0
Verwarmingscapaciteit -10 °C	kW			
Pdesign cap. koelen/verwarmen	kW	8,2/6,1	10,2/8,8	12,0/9,2
Temperatuurbereik koelen		-15~+50°C	-15~+50°C	-15~+50°C
Temperatuurbereik verwarmen		-15~+24°C	-15~+24°C	-15~+24°C
S.E.E.R./S.C.O.P.		7,0/3,8	6,5/3,8	6,8/3,8
Energie label		A++/A+	A++/A	A++/A
Jaarlijks energieverbruik	kW/uur	410/2275	550/3242	618/3390
PED categorie		Art.3 Lid3	Art.3 Lid3	Art.3 Lid3
Aansluitspanning	V/pH/Hz	230/1/50	230/1/50	230/1/50
Opgenomen vermogen	kW	2,54/2,38	3,62/3,1	3,89/3,28
Nominale stroomsterkte	A	11,4/10,7	16,0/13,7	17,2/14,6
Afzekerwaarde	A	20T	20T	20T
Bekabeling tussen binnen- en buitenunit	mm ²	5x1,5	5x1,5	5x2,5
Voedingskabel		buiten	buiten	buiten
Maximale leidingslengte	m	80	80	80
Maximaal hoogteverschil	m	15	15	15
Koelleiding diameters	Inch	1/4"-3/8"(x3) 1/4"x1/2"(x1)	1/4"-3/8"(x3) 1/4"x1/2"(x1)	1/4"-3/8"(x4) 1/4"x1/2"(x1)
Koudemiddel inhoud R32	kg	2,1	2,1	2,4
Buitenunit voorgevuld tot x m	m	30	30	37,5
Extra vulling per meter	g/m	12	12	12
Luchthoeveelheid	m ³ /uur	3800	4000	3850
Geluidsdruk	dB(A)	63	64	64
Geluidsvermogen	dB(A)	70	70	73
Afmetingen (HxBxD)	mm	810x946x410	875x1090x500	875x1090x500
Gewicht	kg	62,0	69,9	73,5