

SCM40-60ZS-W buitendelen (R32)
SCM multi split



Overzicht SCM40-60ZS-W (R32)

Model buitendeel	SCM	40ZS-W	45ZS-W	50ZS-W	60ZS-W
Gegevens buitendeel					
Koelcapaciteit	kW	4,0(1,5~5,9)	4,5(1,5~6,4)	5,0(1,7~7,1)	6,0(1,7~7,5)
Verwarmingscapaciteit	kW	4,5(1,3~6,3)	5,3(1,3~6,5)	6,0(1,0~7,5)	6,8(1,0~7,8)
Verwarmingscapaciteit -10 °C	kW	4,1	4,1	4,7	4,7
Pdesign cap. koelen/verwarmen	kW	4,0/4,1	4,5/4,1	5,0/4,7	6,0/4,7
Temperatuurbereik koelen		-15~+46°C	-15~+46°C	-15~+46°C	-15~+46°C
Temperatuurbereik verwarmen		-15~+24°C	-15~+24°C	-15~+24°C	-15~+24°C
Aantal aansluitbare binnendelen		2	2	3	3
S.E.E.R./S.C.O.P.		9,1/4,7	9,1/4,6	8,8/4,7	8,8/4,7
Energielabel		A+++/A++	A+++/A++	A+++/A++	A+++/A++
Jaarlijks energieverbruik	kW/uur	154/1222	174/1222	199/1430	
E.E.R./C.O.P.		5,00/5,42	4,69/5,00	4,90/5,17	4,55/4,86
Subsidie volgens EIA 2022*		Ja	Ja	Ja	Ja
PED categorie		Art.3 Lid3	Art.3 Lid3	Art.3 Lid3	Art.3 Lid3
Aansluitspanning	V/pH/Hz	220-240/1/50-60	220-240/1/50-60	220-240/1/50-60	220-240/1/50-60
Opgenomen vermogen	kW	0,80/0,83	0,96/1,06	1,02/1,16	1,32/1,40
Nominale stroomsterkte	A	3,5/3,7	4,3/4,7	1,02/1,16	5,8/6,1
Afzekerwaarde	A	16T	16T	16T	16T
Bekabeling tussen binnen- en buitenunit	mm ²	4x1,5 (x2)	4x1,5 (x2)	4x1,5 (x3)	4x1,5 (x3)
Voedingskabel		buiten	buiten	buiten	buiten
Maximale leidinglengte totaal	m	30	30	40	40
Maximale leidinglengte 1 unit	m	25	25	25	25
Maximaal hoogteverschil	m	15	15	15	15
Koelleiding diameters	Inch	1/4"-3/8"(x2)	1/4"-3/8"(x2)	1/4"-3/8"(x3)	1/4"-3/8"(x3)
Koudemiddel inhoud R32	kg	1,4	1,4	1,8	1,8
Buitenunit voorgevuld tot x m	m	20	20	40	40
Extra vulling per meter	g/m	20	20	0	0
Luchthoeveelheid	m ³ /uur	1950	1950	2460	2460
Geluidsdruk (silent mode)	dB(A)	49(44)	50(44)	49(43)	50(43)
Geluidsvermogen	dB(A)	62	63	62	62
Afmetingen (HxBxD)	mm	595x870x290	595x870x290	640x915x290	640x915x290
Gewicht	kg	40,0	40,0	48,5	48,5