



Optional wired remote controller. CZ-RD517C



| NEW! Wall-mounted Etherea | Indoor unit graphite grey | Indoor unit silver | Indoor unit matt white | Cooling capacity | Heating capacity | Connection in. / out. | Sound pressure ¹⁾ | | Dimension / Net weight | Piping diameter |
|---------------------------|---------------------------|--------------------|------------------------|------------------|------------------|-----------------------|------------------------------|-----------------------|--------------------------|-----------------|
| | | | | | | | Cool — Heat (Hi/Lo/Q-Lo) | dB(A) | | |
| 1,6 kW | — | — | CS-MZ16CKE | 1,60 | 2,60 | 4x1,5 | 37/26/21 — 38/27/21 | 295 x 870 x 229 / 10 | 1/4 (6,35) / 3/8 (9,52) | |
| 2,0 kW | CS-XZ20CKEW-H | CS-XZ20CKEW | CS-Z20CKEW | 2,00 | 3,20 | 4x1,5 | 37/26/21 — 38/27/21 | 295 x 870 x 229 / 10 | 1/4 (6,35) / 3/8 (9,52) | |
| 2,5 kW | CS-XZ25CKEW-H | CS-XZ25CKEW | CS-Z25CKEW | 2,50 | 3,60 | 4x1,5 | 41/27/21 — 41/29/21 | 295 x 870 x 229 / 10 | 1/4 (6,35) / 3/8 (9,52) | |
| 3,5 kW ²⁾ | CS-XZ35CKEW-H | CS-XZ35CKEW | CS-Z35CKEW | 3,50 | 4,50 | 4x1,5 | 44/30/21 — 45/35/21 | 295 x 870 x 229 / 11 | 1/4 (6,35) / 3/8 (9,52) | |
| 4,2 kW ³⁾ | CS-XZ42CKEW-H | — | CS-Z42CKEW | 4,20 | 5,60 | 4x1,5 | 44/33/27 — 45/37/31 | 295 x 870 x 229 / 10 | 1/4 (6,35) / 3/8 (9,52) | |
| 5,0 kW ⁴⁾ | — | CS-XZ50CKEW | CS-Z50CKEW | 5,00 | 6,80 | 4x2,5 | 44/39/32 — 46/39/32 | 295 x 1040 x 244 / 12 | 1/4 (6,35) / 3/8 (9,52) | |
| 7,1 kW | — | — | CS-Z71CKEW | 7,10 | 8,70 | 4x2,5 | 49/40/32 — 49/40/32 | 295 x 1040 x 244 / 13 | 1/4 (6,35) / 1/2 (12,70) | |



Optional wired remote controller. CZ-RD517C



| NEW! Wall-mounted TZ super-compact | Indoor unit | Cooling capacity | Heating capacity | Connection in. / out. | Sound pressure ¹⁾ | | Dimension / Net weight | Piping diameter |
|------------------------------------|-------------|------------------|------------------|-----------------------|------------------------------|-----------------------|--------------------------|-----------------|
| | | | | | Cool — Heat (Hi/Lo/Q-Lo) | dB(A) | | |
| 1,6 kW | CS-MTZ16CKE | 1,60 | 2,60 | 4x1,5 | 38/27/22 — 39/28/24 | 290 x 765 x 214 / 9 | 1/4 (6,35) / 3/8 (9,52) | |
| 2,0 kW | CS-TZ20CKEW | 2,00 | 3,20 | 4x1,5 | 39/27/22 — 40/28/23 | 290 x 765 x 214 / 9 | 1/4 (6,35) / 3/8 (9,52) | |
| 2,5 kW | CS-TZ25CKEW | 2,50 | 3,60 | 4x1,5 | 42/28/22 — 44/35/23 | 290 x 765 x 214 / 9 | 1/4 (6,35) / 3/8 (9,52) | |
| 3,5 kW ²⁾ | CS-TZ35CKEW | 3,50 | 4,50 | 4x1,5 | 44/32/22 — 44/35/23 | 290 x 765 x 214 / 9 | 1/4 (6,35) / 3/8 (9,52) | |
| 4,2 kW | CS-TZ42CKEW | 4,20 | 5,60 | 4x1,5 | 44/33/27 — 46/37/30 | 290 x 765 x 214 / 9 | 1/4 (6,35) / 3/8 (9,52) | |
| 5,0 kW | CS-TZ50CKEW | 5,00 | 6,80 | 4x2,5 | 44/39/35 — 46/39/35 | 290 x 765 x 214 / 9 | 1/4 (6,35) / 3/8 (9,52) | |
| 6,0 kW | CS-TZ60CKEW | 6,00 | 8,50 | 4x2,5 | 45/39/36 — 47/39/36 | 295 x 1060 x 249 / 14 | 1/4 (6,35) / 1/2 (12,70) | |
| 7,1 kW | CS-TZ71CKEW | 7,10 | 8,70 | 4x2,5 | 49/40/37 — 49/40/37 | 295 x 1060 x 249 / 15 | 1/4 (6,35) / 1/2 (12,70) | |



Optional wired remote controller. CZ-RD517C




| NEW! Floor console ⁵⁾ | Indoor unit | Cooling capacity | Heating capacity | Connection in. / out. | Sound pressure ⁶⁾ | | Dimension / Net weight | Piping diameter |
|----------------------------------|-------------|------------------|------------------|-----------------------|------------------------------|----------------------|-------------------------|-----------------|
| | | | | | Cool — Heat (Hi/Lo/Q-Lo) | dB(A) | | |
| 2,0 kW | CS-MZ20CFEA | 2,00 | 3,20 | 4x1,5 | 39/27/22 — 39/27/21 | 600 x 750 x 207 / 13 | 1/4 (6,35) / 3/8 (9,52) | |
| 2,5 kW | CS-Z25CFEAW | 2,50 | 3,60 | 4x1,5 | 40/27/22 — 40/27/21 | 600 x 750 x 207 / 13 | 1/4 (6,35) / 3/8 (9,52) | |
| 3,5 kW ²⁾ | CS-Z35CFEAW | 3,50 | 4,50 | 4x1,5 | 41/28/22 — 41/28/21 | 600 x 750 x 207 / 13 | 1/4 (6,35) / 3/8 (9,52) | |
| 5,0 kW | CS-Z50CFEAW | 5,00 | 5,30 | 4x1,5 | 44/33/29 — 48/35/31 | 600 x 750 x 207 / 13 | 1/4 (6,35) / 3/8 (9,52) | |



Optional wired remote controller. CZ-RTC6W



Optional wired remote controller. CZ-RTC6



Panel, white (RAL9003). CZ-KPY4W



Panel, graphite black (RAL9011). CZ-KPY4B

Panels (sold separately)



| 4 way 60x60 cassette* | Indoor unit (Panel CZ-KPY4) | Cooling capacity | Heating capacity | Connection in. / out. | Sound pressure ⁷⁾ | | Dimension / Net weight | | Piping diameter |
|-----------------------|-----------------------------|------------------|------------------|-----------------------|------------------------------|----------------------|------------------------|--------------------------|-----------------|
| | | | | | Cool — Heat (Hi/Lo/Q-Lo) | dB(A) | Indoor H x W x D | Panel H x W x D | |
| 2,0 kW | S-M20PY3E | 2,00 | 3,20 | 4x1,5 | 33/30/27 — 33/30/27 | 243 x 575 x 575 / 15 | 30 x 625 x 625 / 2,8 | 1/4 (6,35) / 3/8 (9,52) | |
| 2,5 kW | S-25PY3E | 2,50 | 3,60 | 4x1,5 | 33/30/27 — 33/30/27 | 243 x 575 x 575 / 15 | 30 x 625 x 625 / 2,8 | 1/4 (6,35) / 3/8 (9,52) | |
| 3,5 kW ²⁾ | S-36PY3E | 3,50 | 4,50 | 4x1,5 | 36/32/27 — 36/32/27 | 243 x 575 x 575 / 15 | 30 x 625 x 625 / 2,8 | 1/4 (6,35) / 3/8 (9,52) | |
| 5,0 kW ⁴⁾ | S-50PY3E | 5,00 | 6,80 | 4x1,5 | 41/36/29 — 41/36/29 | 243 x 575 x 575 / 15 | 30 x 625 x 625 / 2,8 | 1/4 (6,35) / 3/8 (9,52) | |
| 6,0 kW | S-60PY3E | 6,00 | 8,50 | 4x1,5 | 45/39/33 — 45/39/33 | 243 x 575 x 575 / 15 | 30 x 625 x 625 / 2,8 | 3/8 (9,52) / 1/2 (12,70) | |

*Compatible with Commercial control and connectivity accessories only. For detailed information go to the control systems section.



Optional wireless control kit. CZ-RL511D



| NEW! Low static pressure hide-away | Indoor unit | Cooling capacity | Heating capacity | Connection in. / out. | Sound pressure ⁸⁾ | | Dimension / Net weight | Piping diameter |
|------------------------------------|--------------|------------------|------------------|-----------------------|------------------------------|----------------------|--------------------------|-----------------|
| | | | | | Cool — Heat (Hi/Lo/Q-Lo) | dB(A) | | |
| 2,0 kW | CS-MZ20CD3EA | 2,00 | 3,20 | 4x1,5 | 34/29/26 — 36/29/26 | 200 x 750 x 640 / 19 | 1/4 (6,35) / 3/8 (9,52) | |
| 2,5 kW | CS-Z25CD3EAW | 2,50 | 3,60 | 4x1,5 | 35/29/26 — 37/29/26 | 200 x 750 x 640 / 19 | 1/4 (6,35) / 3/8 (9,52) | |
| 3,5 kW ²⁾ | CS-Z35CD3EAW | 3,50 | 4,50 | 4x1,5 | 35/29/26 — 37/29/26 | 200 x 750 x 640 / 19 | 1/4 (6,35) / 3/8 (9,52) | |
| 5,0 kW ⁴⁾ | CS-Z50CD3EAW | 5,00 | 6,80 | 4x1,5 | 41/31/28 — 41/32/29 | 200 x 750 x 640 / 19 | 1/4 (6,35) / 3/8 (9,52) | |
| 6,0 kW | CS-Z60CD3EAW | 6,00 | 8,50 | 4x1,5 | 41/32/29 — 43/34/31 | 200 x 750 x 640 / 19 | 1/4 (6,35) / 1/2 (12,70) | |

1) The sound pressure of the indoor unit shows the value measured of a position of 1 m in front of the main body and 0,8 m below the unit. The sound pressure is measured in accordance with JIS C 9612. Q-Lo: Quiet mode. Lo: The lowest set fan speed. 2) Heating capacity in combination with Free Multi outdoor units except with CU-Z235CBE. In this case, the heating capacity is 4,20 kW. 3) Heating capacity in combination with Free Multi outdoor units except with CU-Z250CBE. In this case, the heating capacity is 5,00 kW. 4) Heating capacity in combination with Free Multi outdoor units except with CU-Z235CBE. In this case, the heating capacity is 5,30 kW. 5) Compatible only with 2 ports R32 outdoor CU-Z235CBE / CU-Z241CBE / CU-Z250CBE. Minimum quantity of connection: 2 indoor units. 6) The sound pressure of the units shows the value measured of a position 1 m in front of the main body and 1 m above floor. The sound pressure is measured in accordance with JIS C 9612. Q-Lo: Quiet mode. Lo: The lowest set fan speed. 7) The sound pressure of the indoor unit shows the value measured of a position of 1,5 m below the unit. The sound pressure is measured in accordance with JIS C 9612. Q-Lo: Quiet mode. Lo: The lowest set fan speed. 8) The sound pressure of the indoor unit shows the value measured of a position of 1,5 m below the unit with 1 m duct on the suction side and 2 m duct on the discharge side. The sound pressure is measured in accordance with JIS C 9612.