

38QUS014-027D8S buitendelen inverter 38QUS multi-split R32



Overzicht 38QUS014-027D8S inverter

Model buitendeel	38QUS	014D8S2	018D8S2-1	021D8S3	027D8S3-1
Gegevens buitendeel					
Koelcapaciteit	kW	4,1	5,2	6,1	7,9
Verwarmingscapaciteit	kW	4,4	5,6	6,6	8,2
Verwarmingscapaciteit -10 °C	kW				
Pdesign cap. koelen/verwarmen	kW	4,1/3,7	5,2/4,3	6,1/5,1	7,9/5,7
Temperatuurbereik koelen		-15~+50°C	-15~+50°C	-15~+50°C	-15~+50°C
Temperatuurbereik verwarmen		-15~+24°C	-15~+24°C	-15~+24°C	-15~+24°C
S.E.E.R./S.C.O.P.		6,8/3,8	6,1/3,8	6,5/3,8	6,1/4,0
Energielabel		A++/A+	A++/A+	A++/A+	A++/A+
Jaarlijks energieverbruik	kW/uur	211/1437	303/1695	329/1890	454/1995
PED categorie		Art.3 Lid3	Art.3 Lid3	Art.3 Lid3	Art.3 Lid3
Aansluitspanning	V/pH/Hz	230/1/50	230/1/50	230/1/50	230/1/50
Opgenomen vermogen	kW	1,28/1,10	1,63/1,36	1,90/1,65	2,45/2,05
Nominale stroomsterkte	A	5,8/5,0	7,3/6,1	8,6/7,5	11,0/9,2
Afzekerwaarde	A	16T	16T	16T	20T
Bekabeling tussen binnen- en buitenunit	mm ²	5x1,5	5x1,5	5x1,5	5x1,5
Voedingskabel		buiten	buiten	buiten	buiten
Maximale leidinglengte	m	40	40	60	60
Maximaal hoogteverschil	m	15	15	15	15
Koelleiding diameters	Inch	1/4"-3/8"(x2)	1/4"-3/8"(x2)	1/4"-3/8"(x3)	1/4"-3/8"(x3)
Koudemiddel inhoud R32	kg	1,0	1,25	1,4	1,72
Buitenunit voorgevuld tot x m	m	15	15	22,5	22,5
Extra vulling per meter	g/m	12	12	12	12
Luchthoeveelheid	m ³ /uur	2200	2200	2700	2700
Geluidsdruk	dB(A)	56	56	58	60
Geluidsvermogen	dB(A)	65	65	66	68
Afmetingen (HxBxD)	mm	554x800x333	554x800x333	702x845x363	702x845x363
Gewicht	kg	32,0	35,5	47,0	51,0