

# 2MXM68A

Heating ·230V 50Hz·

Outdoor unit	Indoor unit	Heating capacity [kW]		Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room ·A·	Room ·B·	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
2MXM68N2V1B 2MXM68A2V1B	1.5	2,70	---	1,20	2,70	4,08	0,34	0,72	1,22	1,55	3,35	5,59	95
	2.0	3,00	---	1,19	3,00	4,09	0,34	0,81	1,28	1,57	3,70	5,64	95
	2.5	3,40	-	1,22	3,40	4,30	0,35	1,02	1,37	1,61	4,72	6,08	95
	3.5	4,30	-	1,33	4,30	4,90	0,37	1,41	1,75	1,67	6,50	7,15	95
	4.2	4,90	-	1,44	4,90	5,70	0,40	1,58	2,04	1,82	7,25	7,15	95
	5.0	5,90	-	1,66	5,90	6,90	0,39	1,92	2,59	1,78	8,78	8,70	95
	6.0	7,20	-	1,88	7,20	8,91	0,37	2,39	2,64	1,69	10,94	12,08	95
	1.5+1.5	1,83	1,83	1,33	3,65	7,38	0,29	0,82	1,83	1,31	3,75	8,38	95
	1.5+2.0	1,76	2,34	1,39	4,10	7,76	0,30	0,94	1,99	1,37	4,31	9,09	95
	1.5+2.5	1,76	2,94	1,65	4,70	7,95	0,36	1,10	2,06	1,63	5,04	9,43	95
	1.5+3.5	1,77	4,13	1,80	5,90	8,50	0,37	1,45	2,35	1,68	6,61	10,74	95
	1.5+4.2	1,79	5,01	1,80	6,80	8,85	0,37	1,72	2,57	1,68	7,88	11,75	95
	1.5+5.0	1,80	6,00	2,18	7,80	10,38	0,45	2,03	2,91	2,06	9,27	13,31	95
	1.5+6.0	1,72	6,88	2,46	8,60	10,58	0,48	2,28	2,67	2,19	10,44	12,21	95
	2.0+2.0	2,40	2,40	1,65	4,80	7,95	0,36	1,01	2,31	1,63	4,63	9,47	95
	2.0+2.5	2,36	2,94	1,65	5,30	8,12	0,36	1,17	2,32	1,63	5,34	9,81	95
	2.0+3.5	2,36	4,14	1,80	6,50	8,67	0,37	1,52	2,43	1,68	6,94	11,12	95
	2.0+4.2	2,39	5,01	1,80	7,40	9,03	0,37	1,83	2,66	1,68	8,38	12,17	95
	2.0+5.0	2,37	5,93	2,18	8,30	10,56	0,45	2,18	3,00	2,06	9,98	13,73	95
	2.0+6.0	2,15	6,45	2,46	8,60	10,75	0,48	2,24	2,74	2,19	10,26	12,55	95
	2.5+2.5	2,95	2,95	1,65	5,90	8,49	0,36	1,33	2,36	1,63	6,08	10,78	95
	2.5+3.5	2,96	4,14	1,89	7,10	9,03	0,38	1,72	2,66	1,72	7,86	12,17	95
	2.5+4.2	2,99	5,01	1,89	8,00	9,29	0,38	2,03	2,82	1,72	9,31	12,93	95
	2.5+5.0	2,87	5,73	2,27	8,60	10,68	0,46	2,24	3,09	2,11	10,26	14,15	95
	2.5+6.0	2,53	6,07	2,55	8,60	10,88	0,50	2,22	2,77	2,28	10,17	12,67	95
	3.5+3.5	4,15	4,15	2,17	8,30	9,38	0,42	2,18	2,86	1,94	9,98	13,09	95
	3.5+4.2	3,91	4,69	2,17	8,60	9,47	0,42	2,26	2,91	1,94	10,35	13,31	95
	3.5+5.0	3,54	5,06	2,56	8,60	10,90	0,51	2,22	3,13	2,32	10,17	14,32	95
3.5+6.0	3,17	5,43	2,74	8,60	11,01	0,52	2,21	2,76	2,37	10,12	12,63	95	
4.2+4.2*	4,30	4,30	2,17	8,60	9,56	0,42	2,22	2,94	1,94	10,17	13,47	95	
4.2+5.0*	3,93	4,67	2,56	8,60	10,91	0,51	2,21	3,19	2,32	10,12	14,61	95	
4.2+6.0*	3,54	5,06	2,74	8,60	11,02	0,51	2,20	2,79	2,32	10,07	12,76	95	

## Notes

- 1) The total capacity of each connected indoor unit is up to ·10.2·kW.
- 2) The values mentioned in this document are for connecting with the following indoor unit types:  
·1.5, 2.0, 2.5, 3.5, 4.2, 5.0, 6.0· kW class  
Wall-mounted ·FTXM-M, FTXM-N, FTXM-R· series  
\* Only for ·CTXM-R· and ·FTXM-R· series
- 3) Heating capacity conditions  
Indoor temperature ·20·°C DB  
Outdoor temperature ·7·°C DB / ·6·°C WB
- 4) For additional information on the connection of the DHW generator for Multi and the Hybrid for Multi, see ·3D106169·.

**4D139798**