

3. Specifications

Model			Indoor	CS-Z25UFEAW			CS-Z35UFEAW		
			Outdoor	CU-Z25UBEA			CU-Z35UBEA		
Performance Test Condition				EUROVENT			EUROVENT		
Power Supply			Phase, Hz	Single, 50			Single, 50		
			V	230			230		
				Min.	Mid.	Max.	Min.	Mid.	Max.
Cooling	Capacity		kW	0.85	2.50	3.40	0.85	3.50	3.80
			BTU/h	2900	8530	11600	2900	11900	13000
			kcal/h	730	2150	2920	730	3010	3270
	Running Current		A	—	2.50	—	—	3.90	—
	Input Power		W	240	520	900	240	860	1.02k
	Annual Consumption		kWh	—	260	—	—	430	—
	EER		W/W	3.54	4.81	3.78	3.54	4.07	3.73
			BTU/hW	12.08	16.40	12.89	12.08	13.84	12.75
			kcal/hW	3.04	4.13	3.24	3.04	3.50	3.21
	ErP	Pdesign	kW	2.5			3.5		
		SEER	(W/W)	7.9			8.1		
		Annual Consumption	kWh	111			151		
		Class		A++			A++		
	Power Factor		%	—	90	—	—	96	—
	Indoor Noise (H / L / QLo)		dB-A	38 / 25 / 20			39 / 26 / 20		
			Power Level dB	54 / — / —			55 / — / —		
	Outdoor Noise (H / L / QLo)		dB-A	46 / — / —			48 / — / —		
			Power Level dB	61 / — / —			63 / — / —		
Heating	Capacity		kW	0.85	3.40	5.00	0.85	4.30	6.00
			BTU/h	2900	11600	17100	2900	14700	20500
			kcal/h	730	2920	4300	730	3700	5160
	Running Current		A	—	3.50	—	—	4.80	—
	Input Power		W	240	760	1.35k	240	1.08k	1.75k
	COP		W/W	3.54	4.47	3.70	3.54	3.98	3.43
			BTU/hW	12.08	15.26	12.67	12.08	13.61	11.71
			kcal/hW	3.04	3.84	3.19	3.04	3.43	2.95
	ErP	Pdesign	kW	2.7			3.2		
		Tbivalent	°C	-10			-10		
		SCOP	(W/W)	4.6			4.6		
		Annual Consumption	kWh	822			974		
		Class		A++			A++		
	Power Factor		%	—	94	—	—	98	—
	Indoor Noise (H / L / QLo)		dB-A	38 / 25 / 19			39 / 26 / 19		
			Power Level dB	54 / — / —			55 / — / —		
	Outdoor Noise (H / L / QLo)		dB-A	47 / — / —			48 / — / —		
			Power Level dB	62 / — / —			63 / — / —		
Low Temp. : Capacity (kW) / I.Power (W) / COP				3.62 / 1.19k / 3.04			4.35 / 1.55k / 2.81		
Extr Low Temp. : Capacity (kW) / I.Power (W) / COP				2.88 / 1.18k / 2.44			3.37 / 1.41k / 2.39		
Max Current (A) / Max Input Power (W)				6.2 / 1.35k			8.0 / 1.75k		
Starting Current (A)				3.50			4.80		

Model				Indoor	CS-Z25UFEAW	CS-Z35UFEAW
				Outdoor	CU-Z25UBEA	CU-Z35UBEA
Compressor	Type				Hermetic Motor (Rotary)	Hermetic Motor (Rotary)
	Motor Type				Brushless (6 poles)	Brushless (6 poles)
	Output Power			W	700	700
Indoor Fan	Type				Cross Flow Fan	Cross Flow Fan
	Material				ASG33	ASG33
	Motor Type				DC / Transistor (8-poles)	DC / Transistor (8-poles)
	Input Power			W	44	44
	Output Power			W	30	30
	Speed	QLo	Cool	rpm	520	520
			Heat	rpm	520	520
		Lo	Cool	rpm	610	630
			Heat	rpm	620	640
		Me	Cool	rpm	790	810
			Heat	rpm	820	840
		Hi	Cool	rpm	990	1000
			Heat	rpm	1030	1040
		SHi	Cool	rpm	1040	1050
			Heat	rpm	1080	1090
Outdoor Fan	Type				Propeller Fan	Propeller Fan
	Material				PP	PP
	Motor Type				DC (8-poles)	DC (8-poles)
	Input Power			W	–	–
	Output Power			W	40	40
	Speed	Hi	Cool	rpm	820	850
			Heat	rpm	780	830
Moisture Removal			L/h (Pt/h)	1.5 (3.2)	2.0 (4.2)	
Indoor Airflow	QLo	Cool	m³/min (ft³/min.)	5.0 (177)	5.0 (177)	
		Heat	m³/min (ft³/min.)	5.0 (177)	5.0 (177)	
	Lo	Cool	m³/min (ft³/min.)	5.8 (205)	6.0 (212)	
		Heat	m³/min (ft³/min.)	5.9 (208)	6.1 (215)	
	Me	Cool	m³/min (ft³/min.)	7.5 (265)	7.7 (272)	
		Heat	m³/min (ft³/min.)	7.8 (275)	8.0 (283)	
	Hi	Cool	m³/min (ft³/min.)	9.60 (340)	9.90 (350)	
		Heat	m³/min (ft³/min.)	9.90 (350)	10.10 (355)	
	SHi	Cool	m³/min (ft³/min.)	9.8 (346)	10.2 (360)	
		Heat	m³/min (ft³/min.)	10.2 (360)	10.5 (371)	
Outdoor Airflow	Hi	Cool	m³/min (ft³/min.)	28.7 (1015)	34.3 (1210)	
		Heat	m³/min (ft³/min.)	27.2 (960)	33.5 (1185)	
Refrigeration Cycle	Control Device			Expansion Valve	Expansion Valve	
	Refrigerant Oil		cm³	FW50S (320)	FW50S (320)	
	Refrigerant Type		g (oz)	R32, 880 (31.1)	R32, 930 (32.8)	
F-Gas	GWP			675	675	
	CO2eq (ton) (Precharged Amount / Maximum Charged Amount)			0.594 / 0.678	0.628 / 0.712	
Dimension	Height (I/D / O/D)		mm (inch)	600 (23-5/8) / 542 (21-11/32)	600 (23-5/8) / 619 (24-3/8)	
	Width (I/D / O/D)		mm (inch)	750 (29-17/32) / 780 (30-23/32)	750 (29-17/32) / 824 (32-15/32)	
	Depth (I/D / O/D)		mm (inch)	207 (8-5/32) / 289 (11-13/32)	207 (8-5/32) / 299 (11-25/32)	

Model		Indoor	CS-Z25UFEAW		CS-Z35UFEAW	
		Outdoor	CU-Z25UBEA		CU-Z35UBEA	
Weight	Net (I/D / O/D)	kg (lb)	13 (29) / 33 (73)		13 (29) / 35 (77)	
Piping	Pipe Diameter (Liquid / Gas)	mm (inch)	6.35 (1/4) / 9.52 (3/8)		6.35 (1/4) / 9.52 (3/8)	
	Standard length	m (ft)	5.0 (16.4)		5.0 (16.4)	
	Length range (min – max)	m (ft)	3 (9.8) ~ 20 (65.6)		3 (9.8) ~ 20 (65.6)	
	I/D & O/D Height different	m (ft)	15.0 (49.2)		15.0 (49.2)	
	Additional Gas Amount	g/m (oz/ft)	10 (0.1)		10 (0.1)	
	Length for Additional Gas	m (ft)	7.5 (24.6)		7.5 (24.6)	
Drain Hose	Inner Diameter	mm	28.5		28.5	
	Length	mm	270		270	
Indoor Heat Exchanger	Fin Material		Aluminium (Pre Coat)		Aluminium (Pre Coat)	
	Fin Type		Slit Fin		Slit Fin	
	Row × Stage × FPI		2 × 17 × 21		2 × 17 × 21	
	Size (W × H × L)	mm	554 × 357 × 25.4		554 × 357 × 25.4	
Outdoor Heat Exchanger	Fin Material		Aluminium		Aluminium	
	Fin Type		Corrugated Fin		Corrugated Fin	
	Row × Stage × FPI		2 × 24 × 19		2 × 28 × 17	
	Size (W × H × L)	mm	36.4 × 504 × 824.2:793.7		36.38 × 588 × 856.3:827.7	
Air Filter	Material		Polypropelene		Polypropelene	
	Type		One-touch		One-touch	
Power Supply			Outdoor		Outdoor	
Power Supply Cord		A	Nil		Nil	
Thermostat			Electronic Control		Electronic Control	
Protection Device			Electronic Control		Electronic Control	
			Dry Bulb	Wet Bulb	Dry Bulb	Wet Bulb
Indoor Operation Range	Cooling	Maximum °C	32	23	32	23
		Minimum °C	16	11	16	11
	Heating	Maximum °C	30	–	30	–
		Minimum °C	16	–	16	–
Outdoor Operation Range	Cooling	Maximum °C	43	26	43	26
		Minimum °C	-10	–	-10	–
	Heating	Maximum °C	24	18	24	18
		Minimum °C	-15	-16	-15	-16

- Cooling capacities are based on indoor temperature of 27°C Dry Bulb (80.6°F Dry Bulb), 19.0°C Wet Bulb (66.2°F Wet Bulb) and outdoor air temperature of 35°C DRY BULB (95°F Dry Bulb), 24°C Wet Bulb (75.2°F Wet Bulb).
- Heating capacities are based on indoor temperature of 20°C Dry Bulb (68°F Dry Bulb) and outdoor air temperature of 7°C Dry Bulb (44.6°F Dry Bulb), 6°C Wet Bulb (42.8°F Wet Bulb).
- Heating low temperature capacity, Input Power and COP measured at 230 V, indoor temperature 20°C, outdoor 2/1°C.
- Heating extreme low temperature capacity, Input Power and COP measured at 230 V, indoor temperature 20°C, outdoor -7/-8°C.
- Standby power consumption ≤10.0w (when switched OFF by remote control, except under self protection control).
- Specifications are subjected to change without prior notice for further improvement.

Model			Indoor	CS-Z50UFEAW		
			Outdoor	CU-Z50UBEA		
Performance Test Condition			EUROVENT			
Power Supply			Phase, Hz	Single, 50		
			V	230		
			Min.	Mid.	Max.	
Cooling	Capacity		kW	0.90	5.00	5.70
			BTU/h	3070	17100	19400
			kcal/h	770	4300	4900
	Running Current		A	–	6.20	–
	Input Power		W	255	1.39k	1.81k
	Annual Consumption		kWh	–	695	–
	EER		W/W	3.53	3.60	3.15
			BTU/hW	12.04	12.30	10.72
			Kcal/hW	3.02	3.09	2.71
	ErP	Pdesign	kW	5.0		
		SEER	(W/W)	6.7		
		Annual Consumption	kWh	261		
		Class		A++		
	Power Factor		%	–	97	–
	Indoor Noise (H / L / QLo)		dB-A	44 / 31 / 27		
			Power Level dB	60 / – / –		
	Outdoor Noise (H / L / QLo)		dB-A	48 / – / –		
			Power Level dB	63 / – / –		
Heating	Capacity		kW	0.90	5.80	8.10
			BTU/h	3070	19800	27600
			kcal/h	770	4990	6970
	Running Current		A	–	7.00	–
	Input Power		W	260	1.55k	2.60k
	COP		W/W	3.46	3.74	3.12
			BTU/hW	11.81	12.77	10.62
			kcal/hW	2.96	3.22	2.68
	ErP	Pdesign	kW	4.4		
		Tbivalent	°C	-10		
		SCOP	(W/W)	4.3		
		Annual Consumption	kWh	1433		
		Class		A+		
	Power Factor		%	–	96	–
	Indoor Noise (H / L / QLo)		dB-A	46 / 33 / 29		
			Power Level dB	62 / – / –		
	Outdoor Noise (H / L / QLo)		dB-A	48 / – / –		
			Power Level dB	63 / – / –		
Low Temp. : Capacity (kW) / I.Power (W) / COP			5.87 / 2.30k / 2.55			
Extr Low Temp. : Capacity (kW) / I.Power (W) / COP			5.03 / 2.06k / 2.44			
Max Current (A) / Max Input Power (W)			11.4 / 2.60k			
Starting Current (A)			7.00			

Model				Indoor	CS-Z50UFEAW	
				Outdoor	CU-Z50UBEA	
Compressor	Type				Hermetic Motor (Rotary)	
	Motor Type				Brushless (4 poles)	
	Output Power			W	900	
Indoor Fan	Type				Cross Flow Fan	
	Material				ASG33	
	Motor Type				DC / Transistor (8-poles)	
	Input Power			W	44	
	Output Power			W	30	
	Speed	QLo	Cool	rpm	670	
			Heat	rpm	740	
		Lo	Cool	rpm	750	
			Heat	rpm	830	
		Me	Cool	rpm	970	
			Heat	rpm	1050	
		Hi	Cool	rpm	1190	
			Heat	rpm	1350	
		SHi	Cool	rpm	1240	
			Heat	rpm	1400	
Outdoor Fan	Type				Propeller Fan	
	Material				PP	
	Motor Type				DC (8-poles)	
	Input Power			W	—	
	Output Power			W	40	
	Speed	Hi	Cool	rpm	720	
			Heat	rpm	700	
Moisture Removal			L/h (Pt/h)	2.8 (5.9)		
Indoor Airflow	QLo	Cool	m³/min (ft³/min.)	6.4 (226)		
		Heat	m³/min (ft³/min.)	7.0 (247)		
	Lo	Cool	m³/min (ft³/min.)	7.1 (251)		
		Heat	m³/min (ft³/min.)	7.9 (279)		
	Me	Cool	m³/min (ft³/min.)	9.2 (325)		
		Heat	m³/min (ft³/min.)	9.9 (350)		
	Hi	Cool	m³/min (ft³/min.)	11.60 (410)		
		Heat	m³/min (ft³/min.)	13.20 (465)		
	SHi	Cool	m³/min (ft³/min.)	12.0 (424)		
		Heat	m³/min (ft³/min.)	13.5 (477)		
Outdoor Airflow	Hi	Cool	m³/min (ft³/min.)	39.7 (1400)		
		Heat	m³/min (ft³/min.)	38.6 (1365)		
Refrigeration Cycle	Control Device			Expansion Valve		
	Refrigerant Oil		cm³	FW50S (450)		
	Refrigerant Type		g (oz)	R32, 1.13k (39.9)		
F-Gas	GWP			675		
	CO2eq (ton) (Precharged Amount / Maximum Charged Amount)			0.763 / 0.991		
Dimension	Height (I/D / O/D)		mm (inch)	600 (23-5/8) / 695 (27-3/8)		
	Width (I/D / O/D)		mm (inch)	750 (29-17/32) / 875 (34-15/32)		
	Depth (I/D / O/D)		mm (inch)	207 (8-5/32) / 320 (12-5/8)		

Model		Indoor	CS-Z50UFEAW	
		Outdoor	CU-Z50UBEA	
Weight	Net (I/D / O/D)	kg (lb)	13 (29) / 43 (95)	
Piping	Pipe Diameter (Liquid / Gas)	mm (inch)	6.35 (1/4) / 12.70 (1/2)	
	Standard length	m (ft)	5.0 (16.4)	
	Length range (min – max)	m (ft)	3 (9.8) ~ 30 (98.4)	
	I/D & O/D Height different	m (ft)	20.0 (65.6)	
	Additional Gas Amount	g/m (oz/ft)	15 (0.2)	
	Length for Additional Gas	m (ft)	7.5 (24.6)	
Drain Hose	Inner Diameter	mm	28.5	
	Length	mm	270	
Indoor Heat Exchanger	Fin Material		Aluminium (Pre Coat)	
	Fin Type		Slit Fin	
	Row × Stage × FPI		2 × 17 × 21	
	Size (W × H × L)	mm	554 × 357 × 25.4	
Outdoor Heat Exchanger	Fin Material		Aluminium	
	Fin Type		Corrugated Fin (Pre Coat)	
	Row × Stage × FPI		2 × 31 × 19	
	Size (W × H × L)	mm	36.4 × 651 × 854.5:824.5	
Air Filter	Material		Polypropelene	
	Type		One-touch	
Power Supply			Outdoor	
Power Supply Cord		A	Nil	
Thermostat			Electronic Control	
Protection Device			Electronic Control	
			Dry Bulb	Wet Bulb
Indoor Operation Range	Cooling	Maximum °C	32	23
		Minimum °C	16	11
	Heating	Maximum °C	30	–
		Minimum °C	16	–
Outdoor Operation Range	Cooling	Maximum °C	43	26
		Minimum °C	-10	–
	Heating	Maximum °C	24	18
		Minimum °C	-15	-16

- Cooling capacities are based on indoor temperature of 27°C Dry Bulb (80.6°F Dry Bulb), 19.0°C Wet Bulb (66.2°F Wet Bulb) and outdoor air temperature of 35°C DRY BULB (95°F Dry Bulb), 24°C Wet Bulb (75.2°F Wet Bulb).
- Heating capacities are based on indoor temperature of 20°C Dry Bulb (68°F Dry Bulb) and outdoor air temperature of 7°C Dry Bulb (44.6°F Dry Bulb), 6°C Wet Bulb (42.8°F Wet Bulb).
- Heating low temperature capacity, Input Power and COP measured at 230 V, indoor temperature 20°C, outdoor 2/1°C.
- Heating extreme low temperature capacity, Input Power and COP measured at 230 V, indoor temperature 20°C, outdoor -7/-8°C.
- Standby power consumption ≤10.0w (when switched OFF by remote control, except under self protection control).
- Specifications are subjected to change without prior notice for further improvement.