



# Silent+ Mini Orange®

## CONDENSATE REMOVAL PUMP

The world's No.1 Orange mini pump is now better than ever. Using our proven 5th Gen Technology, the Silent+ Mini Orange boasts sound levels as low as 16dB(A)\*. So quiet it eliminates the need for additional noise or vibration dampers. Capacitance sensor technology, provides intelligent, adaptive flow rates. Quietly brilliant.


- 35L/h max. flow
- 10m max. rec. head
- As low as 16dB(A)\*

### Key Features

- Proven 5th Gen Technology: Capacitance Sensing & Rotary Diaphragm = Silence & Power
- Low maintenance
- Plug and play\*\*
- 3 year warranty


### Suitability

- Up to 40kW / 136,000Btu/h
- Ducted units; floor standing & chassis units; high wall split systems
- **Perfect for...** small commercial and residential units



0.391 kg

SPECIFICATIONS	
Max. flow	35L/h @ 0m head
Max. rec. head	10m
Max. suction lift	1.5m
Min. dB(A) @ 1m	16dB(A)*
Power supply	100-250VAC, 0.18A, 2.4W, 50/60 Hz
Rated	Continuous
Class	II □
Max. unit output	40kW (136,000Btu/h)
Max. ambient temp	40°C (104°F)
IP Protection	IP24
Inlet o/d	Ø16mm (5/8")
Outlet o/d	Ø6mm (1/4")
Safety switch	5.0 A Normally closed
Self priming	✓



SUGGESTED XTRA ACCESSORIES		
Description		Part No.
Hose Clamp 10.1 dia. (x10)		B3340
S+ Mini Pump spare filters (x10)		FP3330
Barbed anti-siphon device		FP3336/1
Reservoir copper mesh filter (x10)		FP3460

Visit [aspenspumps.com](http://aspenspumps.com) for more installation accessories.

**OPTIONS**  
Silent+ Mini Orange (5th Gen, Europe) FP3430

**IN THE BOX**  
Silent+ Mini Orange 5th Gen pump • Reservoir (inc. filter and lid) • 1.5m plug and play cable\*\*  
• 1.5m clear PVC tube • 150mm clear vent hose  
• 220mm Orange inlet hose • Drain connector kit: straight connector and rubber elbow  
• Quick start guide

Download full manual at [aspenspumps.com](http://aspenspumps.com)

\*Assuming solid wall construction with a 2kW unit  
\*\*Not backwards compatible

Information correct at time of going to press. Not all products are available in all regions.