



SINGLE-SPLIT WALL MOUNTED TYPE



SRK-ZT-WF

New



SRK20,25,35,50ZT-WF

Pure White(-WF)



BUILT IN WIRELESS LAN



Black(-WFB)



Titanium & Black(-WFT)



Wireless remote control

KEY FEATURES

- Elegant, timeless design, ideal for small to medium-sized living spaces
- Available in three different colour preferences
- R32 environmentally friendly refrigerant offers low Global Warming Potential (GWP) and high energy efficiency
- Jet technology ensures quiet air flow and extended reach
- Wireless interface control is integrated as standard

SPECIFICATIONS

Indoor unit			SRK20ZT-WF,-WFB,-WFT	SRK25ZT-WF,-WFB,-WFT	SRK35ZT-WF,-WFB,-WFT	SRK50ZT-WF,-WFB,-WFT
Outdoor unit			SRC20ZT-W,-WB	SRC25ZT-W,-WB	SRC35ZT-W,-WB	SRC50ZT-W,-WB
Power source			1 Phase, 220 - 240V, 50Hz			
Nominal cooling capacity (Min-Max)		kW	2.0 (0.9 - 2.9)	2.5 (0.9 - 3.3)	3.5 (0.9 - 4.0)	5.0 (1.3 - 5.4)
Nominal heating capacity (Min-Max)		kW	2.7 (0.9 - 4.5)	3.2 (0.9 - 4.7)	4.0 (0.9 - 5.0)	5.8 (1.3 - 6.4)
Power consumption	Cooling/Heating	kW	0.42 / 0.53	0.57 / 0.70	0.88 / 0.91	1.43 / 1.48
EER/COP	Cooling/Heating		4.76 / 5.09	4.39 / 4.57	3.98 / 4.40	3.50 / 3.92
Max. running current		A	9	9	9	14.5
Sound power level	Indoor	Cooling/Heating	47 / 49	50 / 52	52 / 55	59 / 59
	Outdoor	Cooling/Heating	55 / 56	56 / 58	62 / 61	63 / 63
Sound pressure level	Indoor	Cooling (Hi/Me/Lo/Ulo)	32 / 25 / 22 / 19	35 / 28 / 23 / 19	38 / 30 / 26 / 19	45 / 36 / 29 / 22
	Outdoor	Cooling/Heating	42 / 43	45 / 46	50 / 48	50 / 51
Air flow	Indoor	Cooling (Hi/Me/Lo/Ulo)	9.0 / 7.0 / 5.9 / 5.0	10.0 / 8.3 / 6.0 / 5.0	10.0 / 8.6 / 6.3 / 5.0	13.3 / 10.0 / 7.6 / 5.7
	Outdoor	Cooling/Heating	9.4 / 8.4 / 6.4 / 5.3	10.6 / 9.0 / 6.5 / 5.3	11.3 / 10.0 / 6.7 / 5.3	13.5 / 10.6 / 8.8 / 6.6
Exterior dimensions	Indoor / Outdoor	Height x Width x Depth	290 x 870 x 230			595 x 780(+62) x 290
Net weight	Indoor / Outdoor	kg	10.5 / 33.0		11.0 / 33.5	11.0 / 33.0
Refrigerant	Type/GWP		R32 / 675			
	Charge	kg/CO ₂ Eq	0.76 / 0.513		0.81 / 0.547	0.83 / 0.560
Refrigerant piping size	Liquid/Gas	ø mm	6.35(1/4") / 9.52(3/8")			6.35(1/4") / 12.7(1/2")
Refrigerant line (one way) length [chargeless length]		m	Max.20 [15]			Max.25 [15]
Vertical height differences	Outdoor is higher/lower	m	Max.15 / Max.15			Max.20 / Max.20
Outdoor operating temperature range	Cooling	°CDB	-15 to 50			
	Heating		-20 to 24			
Clean filter			Allergen Clear Filter x1, Photocatalytic Washable Deodorising Filter x1			

• The data are measured under the following conditions(ISO-T1, H1). Cooling: Indoor temp. of 27°CDB, 19°CWB, and outdoor temp. of 35°CDB. Heating: Indoor temp. of 20°CDB, and outdoor temp. of 7°CDB, 6°CWB.
 • Sound level indicates the value in an anechoic chamber. During operation these values are somewhat higher due to ambient conditions.
 • 'tonne(s) of CO₂ equivalent' means a quantity of greenhouse gases- expressed as the product of the weight of the greenhouse gases in metric tonnes and of their global warming potential.